

Sohal

WELDING RECTIFIERS



SPECIFICATIONS:

ITEM	UNIT	RRL 250	RRL 400
Supply	Volt	415 V \pm 10%	415 V \pm 10%
Phase	No.	3 ϕ	3 ϕ
Frequency	Hertz	50 Hz	50 Hz
KVA	KVA	11 KVA	17 KVA
Open Circuit Voltage	Volt	60 V	65 V
Minimum Welding Current	Amp.	50 A	80 A
Output @ 60% duty cycle	Ampere	250 A	400 A
Output @ 100% duty cycle	Ampere	210 A	340 A
Insulation	Class	'F'	'F'
Weight	Kilogram	140 Kg	170Kg
Overall dimensions(WXHXD)	Millimeter	500 X 780 X 950 mm	530 X 780 X 950 mm

* All specifications are being carried out at 400 Volts 50 Hz.

ACCESSORIES:

Welding Holder + Welding Lead + Work Lead & Welding Screen with Glasses

** In view of continuous research & devolvments, all the specifications are subjected to change without prior notice.*

SOHAL ELECTRIC WORKS

13243, Link Road, Chowk Dholewal, Ludhiana-141003 (PB.).

Phone: +91-0161-2532255, Fax: +91-0161-2531116

E-mail: mail@sohal.org